



SPECIFICATIONS:
 MOTOR: 2HP GEAR-DRIVE MOTOR, 118RPM.
 SEAL: EXTERNALLY-MOUNTED DRY-RUNNING.
 IMPELLER: ϕ 28" 3-BLADE HYDROFOIL.
 MOUNT: 3" TRICLAMP. OTHER SIZES/TYPES
 AVAILABLE UPON REQUEST.
 MATERIALS: 316SS WETTED PARTS

ϕ 28" 3-BLADE
 HYDROFOIL, 316SS

<p>PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INDCO INCORPORATED. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDCO INCORPORATED IS PROHIBITED.</p>			DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL \pm ANGULAR: MACH \pm BEND \pm TWO PLACE DECIMAL \pm THREE PLACE DECIMAL \pm	NAME	DATE	<p>PhG-200T MIXER GENERAL ARRANGEMENT</p>	
				DRAWN	MH		9/20/11
				CHECKED			
			ENG APPR.				
			MFG APPR.				
		MATERIAL		Q.A.		SIZE DWG. NO. REV. A 31Q1047 - PhG-200T 0 SCALE:1:8 WEIGHT: SHEET 1 OF 1	
NEXT ASSY	USED ON	FINISH	COMMENTS:				
APPLICATION		DO NOT SCALE DRAWING					